



AC-9 -- AQUA-SCOOP "Plus"


530 WELLINGTON AVENUE, CRANSTON, RI 02910

AQUA-SCOOP WITH MOUNTING BRACKET, STAINLESS STEEL SCREWS, KELP FILTER, AND SEVEN FEET OF REINFORCED VINYL HOSE

ADVANTAGES

- AQUA-SCOOP PICKS UP WATER WHILE UNDERWAY.
- TUBE SNAPS OUT OF BRACKET WHEN NOT IN USE OR IF HIT BY AN UNDERWATER OBJECT.
- NO HOLE IN BOTTOM OF BOAT OR THRU-HULL INSTALLATION REQUIRED.
- CHECK VALVE ON TOP OF AQUA-SCOOP PREVENTS BACK FLOW AND HOLDS PRIME ON CENTRIFUGAL PUMP.

INSTRUCTIONS:



Mount AQUA-SCOOP as shown, extending it 1/2" below the bottom of the boat. Prevent it from leaving the water by mounting it as deep and close to the center of the transom as possible, while keeping it away from areas of turbulence. Do not mount scoop in front of prop. This will create turbulence and loss of power.

The hose should run continually upward from the AQUA-SCOOP to the bait tank. Avoid ups and downs or loops that could trap air. The pickup tube is glued into the hose, so shorten the hose by cutting it off at the opposite end.

If connecting the hose to an out-of-water centrifugal pump, make sure that there are no air leaks in the system, not even a pin hole, or you will lose prime on the pump. Clamp the hose firmly to the garden hose inlet nipple.